




AHP-3253

Air Conditioner/Heat Exchanger

Air Cooled
Through Mounted
Nema-12, 4, 4X

3 Phase, 240 VAC, 3 Wire Delta
High Efficiency
2973 BTU/HR



FEATURES

- High capacity thermoelectric design
- Power saving air to air heat exchanger mode (ECO-Mode)
- Heavy duty full perimeter mounting
- Lower profile intrusion into enclosure
- Central input cord for easy mounting
- Closed loop design
- Condensate control and evaporation system
- Increased efficiency at higher ambients by as much as 10%
- Virtually maintenance free
- No compressor
- Environmentally friendly and safe
- Stainless Steel exterior housing
- Mounts and operates in any orientation
- Integral temperature controller
- Weight 88 LBS.

CONTROL TEMPERATURES

Active Cooling	35 °C
Heat Exchanger (ECO-Mode)	25 °C
Active Heating	10 °C
Typical Hysteresis	5 °C
Operating Ambient	-40/+65 °C
Operating Enclosure	-10/+60 °C

POWER INPUTS


Voltage, 3 Phase Delta	240 VAC
Current, Active (per phase)	2.9 AMPS
Current , ECO-Mode	0.70 AMP
Frequency	50/60 Hz

PERFORMANCE RATINGS

Cooling (Traditional)	2973 BTU/HR
Cooling (Din 3168)	872 WATTS
Cooling COP (at L35 L35)	0.72
Heating (Traditional)	> 4100 BTU/HR
Heating (Din 3168)	> 1205 WATTS
Heating COP	> 1.0
Heat Exchanger (ECO-Mode)	18 W/°C

INCLUDES

- Power supply
- Temperature controller
- Power saving heat exchanger mode (ECO-Mode)
- Mounting gasket
- Mounting hardware
- Power input cord
- Circuit breaker



CONFIGURATIONS

MODEL	PART NUMBER	NOTES	TEMPERATURE CONTROL	ENVIRONMENT
AHP-3253	0-14JD-0-000	Cool only, industrial fans & power supply	TC-4F	NEMA-12, IP 52
AHP-3253HC	0-14ID-1-000	Heat/Cool, industrial fans & power supply	TC-7F	NEMA-12, IP 52
AHP-3253XE	0-14JD-4-000	Cool only, sealed hot side fans & power supply	TC-4F	NEMA-4, IP 56
AHP-3253XEHC	0-14ID-5-000	Heat/Cool, sealed hot side fans & power supply	TC-7F	NEMA-4, IP 56
AHP-3253X	0-14JD-2-000	Cool only, Mil. grade hot side fans & power supply	TC-4F	NEMA-4X, IP 56
AHP-3253XHC	0-14ID-3-000	Heat/Cool, Mil. grade hot side fans & power supply	TC-7F	NEMA-4X, IP 56

AHP-3253**MOUNTING STYLE**

Through Mounted

ENVIRONMENTS SERVED

NEMA-12 IP 52

NEMA-4,4X IP 56

RATING (TRADITIONAL)


2973 BTU/hr @ 0 °F ΔT

3945 BTU/hr @ +20 °F ΔT


RATING (DIN 3168)

872 Watts L35 L35


480 Watts L35 L50

Equation of line: $y = \Delta T(^{\circ}\text{C})$ $x = \text{Capacity (Watts)}$ Enclosure Air $y = .039x - 34.02$ Cold Sink $y = .029x - 34.02$

Temperature Differential (F)



Air Flow Pattern

DIMENSIONS

Dimensions do not include hardware
 Mounting hardware and gasket included but not shown
 Dimensions: Inches [Millimeters]

Mounting Cutout
 17.20X18.90 [437X480]